

Layflat blu



Series: 0250

For low pressure applications

- High tenacity polyester fiber
- Kink resistance
- Abrasion resistance
- 100 m reel
except model 10"-12" 50 m reel



Pipe specifications

internal diameter	wall thickness	meter weight	coil weight	coil length	coil diameter	coil height	max working pressure
0,75mm / 3/4"	1,40mm	120g/m	12kg	100m	50cm	4cm	10bar / 170psi
25mm / 1"	1,50mm	180g/m	18kg	100m	52cm	5cm	10bar / 170psi
32mm / 1,25"	1,50mm	220g/m	22kg	100m	57cm	6cm	10bar / 170psi
40mm / 1,5"	1,50mm	270g/m	27kg	100m	60cm	7cm	10bar / 170psi
53mm / 2"	1,50mm	300g/m	30kg	100m	61cm	10cm	6bar / 100psi
65mm / 2,5"	1,50mm	360g/m	36kg	100m	62cm	12cm	6bar / 100psi
78mm / 3"	1,55mm	430g/m	43kg	100m	63cm	14cm	4bar / 70psi
105mm / 4"	1,75mm	620g/m	62kg	100m	66cm	17cm	4bar / 70psi
128mm / 5"	1,75mm	860g/m	86kg	100m	69cm	21cm	3bar / 50psi
156,5mm / 6"	2,00mm	1000g/m	100kg	100m	72cm	25cm	3bar / 50psi
207mm / 8"	2,30mm	2000g/m	200kg	100m	89cm	33cm	2,5bar / 40psi

Layflat white

Series: 0250



For low pressure applications

- Polyethylene lay flat pipe with welded outlets
- Lower manpower cost
- Reduced weed growth
- Spacing based on grower's need
- Storage space and transportation savings
- Standard lenght: 100 m



Pipe specifications

internal diameter	wall thickness	spacing outlets	meter weight	coil weight	coil lenght	coil diameter	coil height	max working pressure
78mm / 3"	1.0mm	0,50	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
78mm / 3"	1.0mm	0,70	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
78mm / 3"	1.0mm	0,90	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
78mm / 3"	1.0mm	1,00	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
78mm / 3"	1.0mm	1,40	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
78mm / 3"	1.0mm	1,50	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
78mm / 3"	1.0mm	1,80	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
78mm / 3"	1.0mm	2,00	220g/m	22kg	100m	78cm	14cm	1,5 bar / 25psi
104mm / 4"	1.05mm	0,50	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
104mm / 4"	1.05mm	0,70	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
104mm / 4"	1.05mm	0,90	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
104mm / 4"	1.05mm	1,00	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
104mm / 4"	1.05mm	1,40	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
104mm / 4"	1.05mm	1,50	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
104mm / 4"	1.05mm	1,80	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
104mm / 4"	1.05mm	2,00	360g/m	36kg	100m	80cm	17cm	1,5 bar / 25psi
128mm / 5"	1.10mm	1,40	540g/m	54kg	100m	107cm	21cm	1,5 bar / 25psi
128mm / 5"	1.10mm	1,50	540g/m	54kg	100m	107cm	21cm	1,5 bar / 25psi
156mm / 6"	1.10mm	1,40	600g/m	60kg	100m	110cm	25cm	1,5 bar / 25psi
156mm / 6"	1.10mm	1,50	600g/m	60kg	100m	110cm	25cm	1,5 bar / 25psi

fittings

description	code	size
Lay flat male adaptor 	pm-LMA2 pm-LMA3 pm-LMA4 pm-LMA5 pm-LMA6	2" / 51mm. 3" / 76mm. 4" / 101mm. 5" / 127mm. 6" / 152mm.
Lay flat coupling 	pm-LC2 pm-LC3 pm-LC4 pm-LC5 pm-LC6	2" / 51mm. 3" / 76mm. 4" / 101mm. 5" / 127mm. 6" / 152mm.
Tee male threaded 	PMT16 PMT22	16 x 1½" x 16 22 x 1½" x 22
Elbow male threaded 	PME16 PME22	16 x 1½" 22 x 1½"
Minivalve male threaded 	PMTV16 PMTV22	16 x 1½" x 16 22 x 1½" x 22
Lay flat punch 	PMLP	14mm
Lay flat start connector key 	PMSCLK	14mm
Lay flat fitting key 	PMK	all sizes
Lay flat dripline start connector 	PMSC1 PMSC2	½" x 14mm ¾" x 14mm

